



TECHNOVINYL POLYMERS(I)LTD.  
30, Unique Indl.Estate, Dr.Rajendra Prasad  
Road, Mulund(W), Mumbai-400 080  
Tel.: 022-25930940/41/43/44. Fax: 022-25642577  
Email: [kk\\_group@vsnl.net](mailto:kk_group@vsnl.net) Website: [www.kkthelittlegiant.com](http://www.kkthelittlegiant.com)



## TECHNICAL DATA SHEET

### GRADE NO. 3370 OR FR

### K-FLEX PVC ELASTOMER

ELASTOMERIC MATT FINISH WIRE & CABLE JACKETING COMPOUND  
(PCP / CSP Elastomer Replacement Grade)

PROPERTIES	UNITS	SPECIFIED VALUES
HARDNESS	Shore A	70 (±5)
TENSILE STRENGTH	kg/cm <sup>2</sup>	70
DENSITY	-	1.22
ELONGATION	%	280
COLOR	-	Natural
OZONE RESISTANCE	-	Excellent
USAGE TEMP.	°C	-25 to +100
OIL RESISTANCE	-	Good

#### Features:

- Gel Free Extrusion
- Rubber Looks & Rubber Feel
- Matt Finish
- Good Abrasion Resistance
- Very Good Flexibility
- Soft Touch
- Oil Resistant
- Flame Retardant
- PCP Elastomer Replacement Grade
- CSP Elastomer Replacement Grade

Manufactures Of :

Thermoplastic Elastomers  
Hi Performance PVC Compounds  
PP Compounds  
Speciality Polymers