



TECHNOVINYL POLYMERS(I)LTD.  
30, Unique Indl. Estate, Dr. Rajendra Prasad  
Road, Mulund(W), Mumbai-400 080  
Tel.: 022-25930940/41/43/44. Fax: 022-25642577  
Email: [kk\\_group@vsnl.net](mailto:kk_group@vsnl.net) Website: [www.kkthelittlegiant.com](http://www.kkthelittlegiant.com)



## TECHNICAL DATA SHEET

### K-PRENE HYFLEX

PROPERTIES	UNITS	PRODUCT CODE NO.			
		HF 15	HF 20	HF 25	HF 30
DENSITY		0.89	0.89	0.89	0.89
HARDNESS	Shore A	15 (±5)	20 (±5)	25 (±5)	30 (±5)
TENSILE STRENGTH	MPa	3	4	5.5	6.5
ELONGATION	%	1000	1100	1200	1350
MFI, (230°C/2.16 kg)	Gms/10 min.	26	30	38	44
COLOR	-	Transluscent			

#### Features:

- Food Grade
- Non Toxic
- Elastic Properties
- High Gloss
- Latex Rubber Feel
- Good Mechanical Properties
- Service Temperature -25 to +110°C
- UV Stabilized
- Good Weathering Properties

Manufactures Of :

Thermoplastic Elastomers

Hi Performance PVC Compounds

PP Compounds

Speciality Polymers